

SCAN WIRELESSLY, EASY AS 1-2-3!

1 Connect to Wi-Fi

Note: Ensure that your device is enabled with Wi-Fi mode.



- When Scanner is turned on, wait 20 seconds until indicator blinks.
- Search for "**DIRECT-xxxxxx_iScanAir**" network. (Note: "xxxxxx" is a 6-digit random code.)
- Input 8-digit password "**12345678**". (Note: indicator becomes a steady blue light when connected.)

2 Scan

Note: iScan Air panel may vary slightly depending on your operating system.



- Insert a photo into the front of Scanner.
- Press the **Scan** button.
- Start scanning with a real time preview.

3 Save and Share

Note: iScan Air panel may vary slightly depending on your operating system.



Mac OS

- Press the **Save** button to reveal a 'Save as' dialog box. You can save the image with a chosen file format (JPG or PDF), file name and directory; or press the **Export to iPhoto** button to export the image to iPhoto.



i Other functions

Set Resolution




- Press **Settings** button at the top-left corner to reveal the menu, select the **Resolution** setting: **Standard** or **Fine**.

Cleaning and Calibration

- ✓ **Always** clean Scanner's rollers and lens first before calibration. If cleaning did not improve image quality, then please perform calibration procedures.
- ✓ **Ensure** the Cleaning Board, Cleaning Strip, and Calibration Card are clean and free of dust before use.
- ✓ **Use** a soft cloth dampened with alcohol to remove dirt and stains from the Cleaning Board. Use small drops of alcohol on the cotton side of Cleaning Strip to help clean easily.


Clean Rollers




- Press **Settings** button at the top-left corner to reveal the menu, select the **Clean** setting.
- Insert included Cleaning Board into the front of Scanner.
- Press the **Clean** button.

Clean Lens

- Turn **off** power.
- Insert included Cleaning Strip to the rear of Scanner.
- Gently move the Strip from side to side as many times as necessary.



Calibrate



- Press **Settings** button at the top-left corner to reveal the menu, select the **Calibrate** setting.
- Insert included Calibration Card with the arrow mark facing up into the front of Scanner.
- Press the **Calibrate** button.